







ON  
POWER

ON  
STANDBY

DUAL  
*Rectifier*  
SOLO HEAD

LOOP  
ACTIVE  
MASTER

CLEAN  
LOOP

MASTER

PRESENCE

BASS

MID

TREBLE

GAIN

FT. SW.

INPUT







POWER SUPPLY  
100V 50/60Hz  
100V 50/60Hz

STEREO CHANNEL, MAIN  
STEREO CHANNEL, SUB  
CHANNEL STYLE SELECT

PHONO  
OPTICAL  
INPUT

SPLA 12 RE  
100K  
10K  
10K  
10K  
CE

SLAVE OFF  
SLAVE ON

REAR PANEL  
100V 50/60Hz  
100V 50/60Hz  
100V 50/60Hz  
100V 50/60Hz

100V 50/60Hz  
100V 50/60Hz  
100V 50/60Hz  
100V 50/60Hz

BASS SWITCH  
B.S. B.M.  
CAUTION  
DO NOT TOUCH  
THIS SWITCH  
WHEN THE  
POWER IS ON

STEREO CHANNEL, MAIN  
STEREO CHANNEL, SUB  
CHANNEL STYLE SELECT  
ACTIVER SELECT

REAR PANEL  
100V 50/60Hz  
100V 50/60Hz  
100V 50/60Hz  
100V 50/60Hz

SH-SONIC

SET TO ORANGE  
MODE USING  
FOOT SWITCH OR  
EXT. SWITCH

ORANGE



RED


CHANNEL  
SELECT

ORANGE CHANNEL GAIN



CLEAN  
RHYTHM

NORMAL:  
ORG-VINTAGE RED-HOODERN



RED TO  
VINTAGE

CHANNEL STYLE SELECT

CHIN



EXTERNAL  
SWITCHING



LOOP

SPEAKERS

16 OHM

8 OHM

4 OHM

4 OHM



CE

PATENTED 5,211,790, 5,198,438 AND OTHERS PENDING

HYDRULIC IN PETALUMA, CALIFORNIA

SLAVE LEVEL



SLAVE OUT

LOOP ON  
ORG & RED

ORG  
AUTO

RED  
AUTO

BYPASS  
LOOP

EXT  
SW

LOOP SELECT

IMPORTANT: First, set records with Loop  
Bypass. Then set Slave & Loop. Use  
Master (Org) to 100% for unity gain. With  
an, adjust Slave to match Effect. Use Loop  
Master to return level & fine volume control.  
Mix for effect depth.





6X 420

STR 430

STR 430

BIAS SWITCH

SL6 EL-34

CAUTION!  
BIAS SETTINGS  
MUST MATCH  
TUBES IN USE

WARNING: To reduce risk of fire or electric shock, replace only with same type and rating of tube. Do not expose this unit to wet or dampness.

CAUTION: To reduce the risk of electric shock, do not remove cover for user serviceable parts inside. Refer servicing to qualified personnel.

VACUUM TUBES (NORMAL) SILICON DIODES (Hi-POWER)

RECTIFIER SELECT

MECSA

100 V~  
50 Hz  
4 AMP

SPONGY BOLD

POWER

LOOP ON  
DMS  
RED  
AUTOLOOP OFF  
EXT  
SIN

SELECT

SLAVE LEVEL

SLAVE OUT

IMPORTANT: Prior to servicing with user replacement tubes and external accessories, please disconnect the power supply. When using the external speaker system, please refer to the manual for the correct connection and use to other parts.

SEND LEVEL

SEND

MIX LEVEL

100%

RETURN

CE

DESIGNED IN PETERBROOK, CALIFORNIA

